



Mayor Mike Spano

CITY OF YONKERS

Vincent Pici, P.E., M.P.A.
Commissioner

DEPARTMENT OF HOUSING AND BUILDINGS
87 Nepperhan Avenue, 5th Floor
Yonkers, NY 10701

Building Tel 914 377 6500
Fax 914 377 6521

Housing Tel 914 377 6536
Fax 914 377 6496

**NOTICE OF UTILIZATION OF TRUSS TYPE CONSTRUCTION,
PRE-ENGINEERED WOOD CONSTRUCTION AND/OR TIMBER
CONSTRUCTION IN RESIDENTIAL STRUCTURES**

(In accordance with Title 19 NYCRR Part 1265)

Property Address: _____ Application #: _____

Section: ____ Block: _____ Lot: _____

Property Owner Name: _____

Property Owner Address: _____

Phone #: _____ Email: _____

PLEASE TAKE NOTICE THAT THIS (CHECK ALL THAT APPLY)

- New Residential Structure
- Addition to Existing Residential Structure
- Rehabilitation to Existing Residential Structure

TO BE CONSTRUCTED OR PERFORMED, WILL UTILIZE (CHECK ALL THAT APPLY)

- Truss Type Construction (TT)
- Pre-engineered Wood Construction (PW)
- Timber Construction (TC)

IN THE FOLLOWING LOCATION(S) (CHECK ALL THAT APPLY)

- Floor framing, including girders and beams (F)
- Roof framing (R)
- Floor framing and Roof framing (FR)

Signature: _____ Date: _____

Print Name: _____

Capacity: (CHECK ONE) Owner Owner's Representative

IDENTIFICATION OF BUILDINGS UTILIZING TRUSS TYPE CONSTRUCTION (check appropriate symbol)

	TYPE I NONCOMBUSTIBLE	TYPE II NONCOMBUSTIBLE	TYPE III NONCOMBUSTIBLE EXTERIOR WALLS	TYPE IV HEAVY TIMBER	TYPE V ANY MATERIAL PERMITTED BY	
Floor Construction						Floor Construction
Roof Construction						Roof Construction
Floor & Roof Construction						Floor & Roof Construction

Required Sign Location(s)

Residential Construction

Affixed to electric meter box attached to the exterior of the structure or affixed to the exterior wall of the residential structure at a point immediately adjacent to the electric box or a location likely to be seen by first responders with approval by the authority having jurisdiction.

The construction type designation shall be "I", "II", "III", "IV" or "V" to indicate the construction classification of the structure under section 602 of the BCNYS

DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS TYPE CONSTRUCTION

"F"	FLOOR FRAMING, INCLUDING GIRDERS AND BEAMS
"R"	ROOF FRAMING
"FR"	FLOOR AND ROOF FRAMING

Commercial Construction

Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached to the door, or attached to a sidelight or the face of the building, not more than 12 inches (305 mm) horizontally from the latch side of the door jamb, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Exterior building entrance doors, exterior exit discharge doors, and exterior roof access doors to a stairway	Attached at each end of the row of doors and at a maximum horizontal distance of 12 feet (3.65M) between signs, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.
Fire department hose connections	Attached to the face of the building, not more than 12 inches (305 mm) horizontally from the center line of the fire department hose connection, and not less than 42 inches (1067 mm) nor more than 60 inches (1524 mm) above the adjoining walking surface.

DESIGNATION FOR STRUCTURAL COMPONENTS THAT ARE OF TRUSS CONSTRUCTION